



Lithium Polymer cells

Lithium Polymer standard series pouch batteries. A flexible solution for a wide range of devices such as wireless applications or as emergency backup.

The Lithium Polymer standard series are designed with a low self-discharge for a long cycle life. The cells are thin and lightweight, plus the moldable and customizable design makes them perfect for a countless number of application areas.

FEATURES

- Low self-discharge
- Thin and light weight
- Moldable and customizable design
- CE, UL, IEC62133, UN 38.3 and RoHS certified
- High energy density

APPLICATIONS

- IoT
- Powerbanks
- Wireless controllers
- Wireless headphones
- Radio controlled equipment and aircrafts
- Mobile devices
- Electric vehicles
- Laptops
- Portable media players

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**1018	KPL381018	3,7	35	3.8 ±0.2	10.0 ±0.5	18.0 ±1.5	0,9
	KPL431018	3,7	50	4.3 ±0.2	10.0 ±0.5	18.0 ±1.5	1,0
**1020	KPL251020	3,7	25	2.5 ±0.2	10.0 ±0.5	20.0 ±1.5	0,8
	KPL301020	3,7	30	3.0 ±0.2	10.0 ±0.5	20.0 ±1.5	0,9
	KPL401020	3,7	55	4.0 ±0.2	10.0 ±0.5	20.0 ±1.5	1,1
**1024	KPL321024	3,7	50	3.2 ±0.2	10.0 ±0.5	24.0 ±1.5	1,2
**1029	KPL411029	3,7	85	4.1 ±0.2	10.0 ±0.5	29.0 ±1.5	1,8
**1030	KPL301030	3,7	60	3.0 ±0.2	10.0 ±0.5	30.0 ±1.5	1,5
	KPL331030	3,7	70	3.3 ±0.2	10.0 ±0.5	30.0 ±1.5	1,6
	KPL401030	3,7	90	4.0 ±0.2	10.0 ±0.5	30.0 ±1.5	1,9
**1033	KPL301033	3,7	70	3.0 ±0.2	10.0 ±0.5	33.0 ±1.5	1,7
**1035	KPL251035	3,7	55	2.5 ±0.2	10.0 ±0.5	35.0 ±1.5	1,7
	KPL321035	3,7	75	3.2 ±0.2	10.0 ±0.5	35.0 ±1.5	1,8
	KPL431035	3,7	110	4.3 ±0.2	10.0 ±0.5	35.0 ±1.5	2,5
**1039	KPL401039	3,7	120	4.0 ±0.2	10.0 ±0.5	39.0 ±1.5	2,6
**1048	KPL301048	3,7	100	3.0 ±0.2	10.0 ±0.5	48.0 ±1.5	3,2
**1050	KPL601050	3,7	250	6.0 ±0.2	10.0 ±0.5	50.0 ±1.5	4,8
**1055	KPL331055	3,7	120	3.3 ±0.2	10.0 ±0.5	55.0 ±1.5	3,3
**1058	KPL371058	3,7	160	3.7 ±0.2	10.0 ±0.5	58.0 ±1.5	3,9
**1120	KPL381120	3,7	50	3.8 ±0.2	11.0 ±0.5	20.0 ±1.5	1,2
	KPL401120	3,7	55	4.0 ±0.2	11.0 ±0.5	20.0 ±1.5	1,3
**1124	KPL231124	3,7	25	2.3 ±0.2	11.0 ±0.5	24.0 ±1.5	1,0
	KPL281124	3,7	45	2.8 ±0.2	11.0 ±0.5	24.0 ±1.5	1,2
	KPL451124	3,7	85	4.5 ±0.2	11.0 ±0.5	24.0 ±1.5	1,7
**1132	KPL301132	3,7	80	3.0 ±0.2	11.0 ±0.5	32.0 ±1.5	1,8
**1165	KPL431165	3,7	250	4.3 ±0.2	11.0 ±0.5	65.0 ±1.5	5,7

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**1218	KPL501218	3,7	60	5.0 ±0.2	12.0 ±0.5	18.0 ±1.5	1,4
**1219	KPL351219	3,7	45	3.5 ±0.2	12.0 ±0.5	19.0 ±1.5	1,2
	KPL481219	3,7	70	4.8 ±0.2	12.0 ±0.5	19.0 ±1.5	1,4
**1220	KPL301220	3,7	40	3.0 ±0.2	12.0 ±0.5	20.0 ±1.5	1,1
	KPL401220	3,7	65	4.0 ±0.2	12.0 ±0.5	20.0 ±1.5	1,3
	KPL451220	3,7	70	4.5 ±0.2	12.0 ±0.5	20.0 ±1.5	1,5
	KPL481220	3,7	80	4.8 ±0.2	12.0 ±0.5	20.0 ±1.5	1,6
	KPL601220	3,7	100	6.0 ±0.2	12.0 ±0.5	20.0 ±1.5	1,8
**1222	KPL281222	3,7	45	2.8 ±0.2	12.0 ±0.5	22.0 ±1.5	1,1
**1223	KPL381223	3,7	65	3.8 ±0.2	12.0 ±0.5	23.0 ±1.5	1,5
**1225	KPL401225	3,7	90	4.0 ±0.2	12.0 ±0.5	25.0 ±1.5	1,8
	KPL451225	3,7	100	4.5 ±0.2	12.0 ±0.5	25.0 ±1.5	2,0
**1229	KPL451229	3,7	105	4.5 ±0.2	12.0 ±0.5	29.0 ±1.5	2,5
**1230	KPL201230	3,7	30	2.0 ±0.2	12.0 ±0.5	30.0 ±1.5	1,4
	KPL351230	3,7	80	3.5 ±0.2	12.0 ±0.5	30.0 ±1.5	2,0
	KPL401230	3,7	100	4.0 ±0.2	12.0 ±0.5	30.0 ±1.5	2,3
	KPL431230	3,7	125	4.3 ±0.2	12.0 ±0.5	30.0 ±1.5	2,4
	KPL501230	3,7	130	5.0 ±0.2	12.0 ±0.5	30.0 ±1.5	2,8
	KPL601230	3,7	160	6.0 ±0.2	12.0 ±0.5	30.0 ±1.5	3,3
**1235	KPL251235	3,7	70	2.5 ±0.2	12.0 ±0.5	35.0 ±1.5	1,8
	KPL401235	3,7	120	4.0 ±0.2	12.0 ±0.5	35.0 ±1.5	2,8
	KPL501235	3,7	150	5.0 ±0.2	12.0 ±0.5	35.0 ±1.5	3,5
	KPL551235	3,7	180	5.5 ±0.2	12.0 ±0.5	35.0 ±1.5	3,8
	KPL601235	3,7	200	6.0 ±0.2	12.0 ±0.5	35.0 ±1.5	4,0
**1239	KPL381239	3,7	130	3.8 ±0.2	12.0 ±0.5	39.0 ±1.5	3,1
	KPL401239	3,7	135	4.0 ±0.2	12.0 ±0.5	39.0 ±1.5	3,2

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**1240	KPL501240	3,7	170	5.0 ±0.2	12.0 ±0.5	40.0 ±1.5	4,0
	KPL701240	3,7	260	7.0 ±0.2	12.0 ±0.5	40.0 ±1.5	5,4
**1245	KPL451245	3,7	200	4.5 ±0.2	12.0 ±0.5	45.0 ±1.5	4,2
	KPL701245	3,7	300	7.0 ±0.2	12.0 ±0.5	45.0 ±1.5	6,0
**1416	KPL451416	3,7	50	4.5 ±0.2	14.0 ±0.5	16.0 ±1.5	1,2
**1417	KPL551417	3,7	70	5.5 ±0.2	14.0 ±0.5	17.0 ±1.5	1,6
**1419	KPL251419	3,7	35	2.5 ±0.2	14.0 ±0.5	19.0 ±1.5	1,0
**1421	KPL401421	3,7	80	4.0 ±0.2	14.0 ±0.5	21.0 ±1.5	1,7
**1422	KPL451422	3,7	95	4.5 ±0.2	14.0 ±0.5	22.0 ±1.5	2,0
**1428	KPL301428	3,7	80	3.0 ±0.2	14.0 ±0.5	28.0 ±1.5	2,0
	KPL401428	3,7	110	4.0 ±0.2	14.0 ±0.5	28.0 ±1.5	2,5
	KPL421428	3,7	120	4.2 ±0.2	14.0 ±0.5	28.0 ±1.5	2,7
**1429	KPL701429	3,7	220	7.0 ±0.2	14.0 ±0.5	29.0 ±1.5	4,3
**1430	KPL451430	3,7	150	4.5 ±0.2	14.0 ±0.5	30.0 ±1.5	3,0
	KPL551430	3,7	180	5.5 ±0.2	14.0 ±0.5	30.0 ±1.5	3,7
	KPL651430	3,7	210	6.5 ±0.2	14.0 ±0.5	30.0 ±1.5	4,5
**1435	KPL501435	3,7	200	5.0 ±0.2	14.0 ±0.5	35.0 ±1.5	4,2
	KPL701435	3,7	300	7.0 ±0.2	14.0 ±0.5	35.0 ±1.5	5,5
**1439	KPL701439	3,7	320	7.0 ±0.2	14.0 ±0.5	39.0 ±1.5	6,3
**1515	KPL401515	3,7	48	4.0 ±0.2	15.0 ±0.5	15.0 ±1.5	1,1
	KPL661515	3,7	85	6.6 ±0.2	15.0 ±0.5	15.0 ±1.5	1,5
**1518	KPL751518	3,7	130	7.5 ±0.2	15.0 ±0.5	18.0 ±1.5	2,3
**1525	KPL321525	3,7	80	3.2 ±0.2	15.0 ±0.5	25.0 ±1.5	1,9
**1528	KPL451528	3,7	120	4.5 ±0.2	15.0 ±0.5	28.0 ±1.5	3,0
	KPL501528	3,7	150	5.0 ±0.2	15.0 ±0.5	28.0 ±1.5	3,3
	KPL571528	3,7	190	5.7 ±0.2	15.0 ±0.5	28.0 ±1.5	4,5

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**1528	KPL701528	3,7	200	7.0 ±0.2	15.0 ±0.5	28.0 ±1.5	4,5
**1537	KPL501537	3,7	230	5.0 ±0.2	15.0 ±0.5	37.0 ±1.5	4,8
	KPL601537	3,7	260	6.0 ±0.2	15.0 ±0.5	37.0 ±1.5	5,6
**1550	KPL401550	3,7	280	4.0 ±0.2	15.0 ±0.5	50.0 ±1.5	5,5
**1575	KPL451575	3,7	450	4.5 ±0.2	15.0 ±0.5	75.0 ±1.5	9,8
**1624	KPL481624	3,7	120	4.8 ±0.2	16.0 ±0.5	24.0 ±1.5	2,9
**1630	KPL501630	3,7	200	5.0 ±0.2	16.0 ±0.5	30.0 ±1.5	4,0
**1643	KPL361643	3,7	200	3.6 ±0.2	16.0 ±0.5	43.0 ±1.5	4,6
	KPL501643	3,7	280	5.0 ±0.2	16.0 ±0.5	43.0 ±1.5	6,2
	KPL551643	3,7	330	5.5 ±0.2	16.0 ±0.5	43.0 ±1.5	6,9
	KPL651643	3,7	380	6.5 ±0.2	16.0 ±0.5	43.0 ±1.5	7,9
	KPL701643	3,7	400	7.0 ±0.2	16.0 ±0.5	43.0 ±1.5	8,4
	KPL751643	3,7	430	7.5 ±0.2	16.0 ±0.5	43.0 ±1.5	8,8
**1646	KPL501646	3,7	300	5.0 ±0.2	16.0 ±0.5	46.0 ±1.5	6,8
	KPL631646	3,7	430	6.3 ±0.2	16.0 ±0.5	46.0 ±1.5	8,2
	KPL781646	3,7	550	7.8 ±0.2	16.0 ±0.5	46.0 ±1.5	10,0
	KPL851646	3,7	600	8.5 ±0.2	16.0 ±0.5	46.0 ±1.5	10,5
**1719	KPL851719	3,7	200	8.5 ±0.2	17.0 ±0.5	19.0 ±1.5	3,4
**1723	KPL651723	3,7	150	6.5 ±0.2	17.0 ±0.5	23.0 ±1.5	3,7
**1725	KPL451725	3,7	120	4.5 ±0.2	17.0 ±0.5	25.0 ±1.5	3,0
	KPL651725	3,7	220	6.5 ±0.2	17.0 ±0.5	25.0 ±1.5	4,2
**1730	KPL251730	3,7	95	2.5 ±0.2	17.0 ±0.5	30.0 ±1.5	2,2
	KPL301730	3,7	120	3.0 ±0.2	17.0 ±0.5	30.0 ±1.5	2,7
	KPL401730	3,7	160	4.0 ±0.2	17.0 ±0.5	30.0 ±1.5	3,4
	KPL451730	3,7	180	4.5 ±0.2	17.0 ±0.5	30.0 ±1.5	3,8
	KPL551730	3,7	250	5.5 ±0.2	17.0 ±0.5	30.0 ±1.5	4,7

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**1730	KPL651730	3,7	280	6.5 ±0.2	17.0 ±0.5	30.0 ±1.5	5,4
	KPL751730	3,7	330	7.5 ±0.2	17.0 ±0.5	30.0 ±1.5	6,0
**1737	KPL501737	3,7	230	5.0 ±0.2	17.0 ±0.5	37.0 ±1.5	5,6
**1738	KPL961738	3,7	500	9.6 ±0.2	17.0 ±0.5	38.0 ±1.5	10,3
**1740	KPL501740	3,7	300	5.0 ±0.2	17.0 ±0.5	40.0 ±1.5	6,1
	KPL681740	3,7	420	6.8 ±0.2	17.0 ±0.5	40.0 ±1.5	8,0
	KPL801740	3,7	470	8.0 ±0.2	17.0 ±0.5	40.0 ±1.5	8,3
**1752	KPL331752	3,7	260	3.3 ±0.2	17.0 ±0.5	52.0 ±1.5	5,6
	KPL351752	3,7	280	3.5 ±0.2	17.0 ±0.5	52.0 ±1.5	6,0
	KPL381752	3,7	300	3.8 ±0.2	17.0 ±0.5	52.0 ±1.5	6,1
	KPL551752	3,7	450	5.5 ±0.2	17.0 ±0.5	52.0 ±1.5	9,3
	KPL601752	3,7	470	6.0 ±0.2	17.0 ±0.5	52.0 ±1.5	9,7
	KPL801752	3,7	730	8.0 ±0.2	17.0 ±0.5	52.0 ±1.5	12,7
**1772	KPL631772	3,7	800	6.3 ±0.2	17.0 ±0.5	72.0 ±1.5	14,7
**1818	KPL801818	3,7	170	8.0 ±0.2	18.0 ±0.5	18.0 ±1.5	3,1
**1830	KPL401830	3,7	175	4.0 ±0.2	18.0 ±0.5	30.0 ±1.5	3,6
**1834	KPL401834	3,7	200	4.0 ±0.2	18.0 ±0.5	34.0 ±1.5	4,2
	KPL461834	3,7	230	4.6 ±0.2	18.0 ±0.5	34.0 ±1.5	4,8
	KPL701834	3,7	380	7.0 ±0.2	18.0 ±0.5	34.0 ±1.5	7,3
**1838	KPL551838	3,7	330	5.5 ±0.2	18.0 ±0.5	38.0 ±1.5	6,8
**1866	KPL501866	3,7	420	5.0 ±0.2	18.0 ±0.5	66.0 ±1.5	11,8
**1885	KPL451885	3,7	730	4.5 ±0.2	18.0 ±0.5	85.0 ±1.5	13,9
**1920	KPL381920	3,7	90	3.8 ±0.2	19.0 ±0.5	20.0 ±1.5	2,1
**1927	KPL801927	3,7	320	8.0 ±0.2	19.0 ±0.5	27.0 ±1.5	6,3
**1936	KPL681936	3,7	430	6.8 ±0.2	19.0 ±0.5	36.0 ±1.5	8,0
**1938	KPL651938	3,7	420	6.5 ±0.2	19.0 ±0.5	38.0 ±1.5	8,2

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**2020	KPL402020	3,7	100	4.0 ±0.2	20.0 ±0.5	20.0 ±1.5	2,3
	KPL502020	3,7	150	5.0 ±0.2	20.0 ±0.5	20.0 ±1.5	2,8
	KPL602020	3,7	180	6.0 ±0.2	20.0 ±0.5	20.0 ±1.5	3,3
	KPL702020	3,7	200	7.0 ±0.2	20.0 ±0.5	20.0 ±1.5	3,8
**2022	KPL762022	3,7	260	7.6 ±0.2	20.0 ±0.5	22.0 ±1.5	4,8
**2023	KPL302023	3,7	80	3.0 ±0.2	20.0 ±0.5	23.0 ±1.5	2,2
	KPL402023	3,7	125	4.0 ±0.2	20.0 ±0.5	23.0 ±1.5	2,8
	KPL452023	3,7	150	4.5 ±0.2	20.0 ±0.5	23.0 ±1.5	3,2
	KPL652023	3,7	240	6.5 ±0.2	20.0 ±0.5	23.0 ±1.5	4,4
**2025	KPL302025	3,7	100	3.0 ±0.2	20.0 ±0.5	25.0 ±1.5	2,5
	KPL352025	3,7	130	3.5 ±0.2	20.0 ±0.5	25.0 ±1.5	2,8
	KPL402025	3,7	140	4.0 ±0.2	20.0 ±0.5	25.0 ±1.5	3,2
	KPL432025	3,7	160	4.3 ±0.2	20.0 ±0.5	25.0 ±1.5	3,4
	KPL532025	3,7	200	5.3 ±0.2	20.0 ±0.5	25.0 ±1.5	4,1
	KPL602025	3,7	240	6.0 ±0.2	20.0 ±0.5	25.0 ±1.5	4,6
	KPL802025	3,7	320	8.0 ±0.2	20.0 ±0.5	25.0 ±1.5	6,0
**2028	KPL502028	3,7	220	5.0 ±0.2	20.0 ±0.5	28.0 ±1.5	4,6
**2030	KPL182030	3,7	45	1.8 ±0.2	20.0 ±0.5	30.0 ±1.5	2,0
	KPL302030	3,7	130	3.0 ±0.2	20.0 ±0.5	30.0 ±1.5	3,1
	KPL352030	3,7	160	3.5 ±0.2	20.0 ±0.5	30.0 ±1.5	3,6
	KPL402030	3,7	200	4.0 ±0.2	20.0 ±0.5	30.0 ±1.5	4,2
	KPL482030	3,7	150	4.8 ±0.2	20.0 ±0.5	30.0 ±1.5	4,9
	KPL582030	3,7	300	5.8 ±0.2	20.0 ±0.5	30.0 ±1.5	5,7
	KPL702030	3,7	360	7.0 ±0.2	20.0 ±0.5	30.0 ±1.5	6,9
	KPL802030	3,7	390	8.0 ±0.2	20.0 ±0.5	30.0 ±1.5	7,7
	KPL902030	3,7	480	9.0 ±0.2	20.0 ±0.5	30.0 ±1.5	8,5

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**2033	KPL102033	3,7	600	1.0 ±0.2	20.0 ±0.5	33.0 ±1.5	10,5
**2035	KPL402035	3,7	240	4.0 ±0.2	20.0 ±0.5	35.0 ±1.5	4,9
	KPL502035	3,7	280	5.0 ±0.2	20.0 ±0.5	35.0 ±1.5	6,2
	KPL552035	3,7	350	5.5 ±0.2	20.0 ±0.5	35.0 ±1.5	6,8
	KPL102035	3,7	600	10.0 ±0.2	20.0 ±0.5	35.0 ±1.5	11,5
**2036	KPL802036	3,7	500	8.0 ±0.2	20.0 ±0.5	36.0 ±1.5	9,8
**2040	KPL402040	3,7	280	4.0 ±0.2	20.0 ±0.5	40.0 ±1.5	6,0
	KPL452040	3,7	320	4.5 ±0.2	20.0 ±0.5	40.0 ±1.5	6,6
	KPL502040	3,7	370	5.0 ±0.2	20.0 ±0.5	40.0 ±1.5	7,4
	KPL552040	3,7	380	5.5 ±0.2	20.0 ±0.5	40.0 ±1.5	7,8
	KPL602040	3,7	420	6.0 ±0.2	20.0 ±0.5	40.0 ±1.5	8,6
	KPL652040	3,7	450	6.5 ±0.2	20.0 ±0.5	40.0 ±1.5	9,4
	KPL702040	3,7	480	7.0 ±0.2	20.0 ±0.5	40.0 ±1.5	10,0
	KPL802040	3,7	580	8.0 ±0.2	20.0 ±0.5	40.0 ±1.5	11,2
	KPL852040	3,7	650	8.5 ±0.2	20.0 ±0.5	40.0 ±1.5	11,8
**2048	KPL452048	3,7	400	4.5 ±0.2	20.0 ±0.5	48.0 ±1.5	8,2
	KPL752048	3,7	670	7.5 ±0.2	20.0 ±0.5	48.0 ±1.5	1,5
**2060	KPL402060	3,7	350	4.0 ±0.2	20.0 ±0.5	60.0 ±1.5	9,3
	KPL102060	3,7	1100	10.0 ±0.2	20.0 ±0.5	60.0 ±1.5	22,4
**2065	KPL352065	3,7	400	3.5 ±0.2	20.0 ±0.5	65.0 ±1.5	9,0
**2068	KPL502068	3,7	650	5.0 ±0.2	20.0 ±0.5	68.0 ±1.5	13,5
**2079	KPL462079	3,7	800	4.6 ±0.2	20.0 ±0.5	79.0 ±1.5	14,5
**2126	KPL922126	3,7	400	9.2 ±0.2	21.0 ±0.5	26.0 ±1.5	7,6
**2222	KPL302222	3,7	100	3.0 ±0.2	22.0 ±0.5	22.0 ±1.5	2,3
**2238	KPL752238	3,7	600	7.5 ±0.2	22.0 ±0.5	38.0 ±1.5	11,0
*2240	KPL552240	3,7	450	5.5 ±0.2	22.0 ±0.5	40.0 ±1.5	8,8

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**2240	KPL752240	3,7	650	7.5 ±0.2	22.0 ±0.5	40.0 ±1.5	11,7
**2244	KPL602244	3,7	540	6.0 ±0.2	22.0 ±0.5	44.0 ±1.5	10,7
**2248	KPL252248	3,7	200	2.5 ±0.2	22.0 ±0.5	48.0 ±1.5	4,5
	KPL502248	3,7	500	5.0 ±0.2	22.0 ±0.5	48.0 ±1.5	10,2
	KPL752248	3,7	750	7.5 ±0.2	22.0 ±0.5	48.0 ±1.5	14,6
	KPL802248	3,7	800	8.0 ±0.2	22.0 ±0.5	48.0 ±1.5	15,7
	KPL902248	3,7	900	9.0 ±0.2	22.0 ±0.5	48.0 ±1.5	17,5
**2260	KPL482260	3,7	600	4.8 ±0.2	22.0 ±0.5	60.0 ±1.5	12,6
**2294	KPL802294	3,7	1650	8.0 ±0.2	22.0 ±0.5	94.0 ±1.5	33,8
**2323	KPL302323	3,7	130	3.0 ±0.2	23.0 ±0.5	23.0 ±1.5	2,6
	KPL362323	3,7	165	3.6 ±0.2	23.0 ±0.5	23.0 ±1.5	3,0
	KPL902323	3,7	400	9.0 ±0.2	23.0 ±0.5	23.0 ±1.5	6,8
**2325	KPL502325	3,7	250	5.0 ±0.2	23.0 ±0.5	25.0 ±1.5	4,6
**2332	KPL662332	3,7	420	6.6 ±0.2	23.0 ±0.5	32.0 ±1.5	8,2
**2335	KPL252335	3,7	150	2.5 ±0.2	23.0 ±0.5	35.0 ±1.5	3,7
	KPL652335	3,7	450	6.5 ±0.2	23.0 ±0.5	35.0 ±1.5	9,2
	KPL752335	3,7	550	7.5 ±0.2	23.0 ±0.5	35.0 ±1.5	10,4
**2338	KPL482338	3,7	360	4.8 ±0.2	23.0 ±0.5	38.0 ±1.5	7,7
	KPL602338	3,7	480	6.0 ±0.2	23.0 ±0.5	38.0 ±1.5	9,4
	KPL652338	3,7	500	6.5 ±0.2	23.0 ±0.5	38.0 ±1.5	10,3
**2339	KPL302339	3,7	240	3.0 ±0.2	23.0 ±0.5	39.0 ±1.5	5,1
	KPL422339	3,7	330	4.2 ±0.2	23.0 ±0.5	39.0 ±1.5	7,0
	KPL452339	3,7	350	4.5 ±0.2	23.0 ±0.5	39.0 ±1.5	7,5
	KPL502339	3,7	420	5.0 ±0.2	23.0 ±0.5	39.0 ±1.5	8,3
	KPL562339	3,7	460	5.6 ±0.2	23.0 ±0.5	39.0 ±1.5	9,3
	KPL882339	3,7	750	8.8 ±0.2	23.0 ±0.5	39.0 ±1.5	14,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeffartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**2425	KPL602425	3,7	255	6.0 ±0.2	24.0 ±0.5	25.0 ±1.5	5,6
**2487	KPL252487	3,7	370	2.5 ±0.2	24.0 ±0.5	87.0 ±1.5	10,8
**2523	KPL652523	3,7	280	6.5 ±0.2	25.0 ±0.5	23.0 ±1.5	5,7
**2525	KPL402525	3,7	200	4.0 ±0.2	25.0 ±0.5	25.0 ±1.5	4,0
	KPL462525	3,7	230	4.6 ±0.2	25.0 ±0.5	25.0 ±1.5	4,6
	KPL602525	3,7	300	6.0 ±0.2	25.0 ±0.5	25.0 ±1.5	5,9
	KPL802525	3,7	400	8.0 ±0.2	25.0 ±0.5	25.0 ±1.5	7,7
**2530	KPL252530	3,7	150	2.5 ±0.2	25.0 ±0.5	30.0 ±1.5	3,3
	KPL402530	3,7	250	4.0 ±0.2	25.0 ±0.5	30.0 ±1.5	5,2
	KPL452530	3,7	280	4.5 ±0.2	25.0 ±0.5	30.0 ±1.5	5,8
	KPL502530	3,7	330	5.0 ±0.2	25.0 ±0.5	30.0 ±1.5	6,5
	KPL652530	3,7	400	6.5 ±0.2	25.0 ±0.5	30.0 ±1.5	8,3
	KPL702530	3,7	500	7.0 ±0.2	25.0 ±0.5	30.0 ±1.5	8,5
**2533	KPL352533	3,7	245	3.5 ±0.2	25.0 ±0.5	33.0 ±1.5	5,3
	KPL452533	3,7	350	4.5 ±0.2	25.0 ±0.5	33.0 ±1.5	6,6
	KPL502533	3,7	370	5.0 ±0.2	25.0 ±0.5	33.0 ±1.5	7,3
	KPL602533	3,7	450	6.0 ±0.2	25.0 ±0.5	33.0 ±1.5	8,6
	KPL652533	3,7	500	6.5 ±0.2	25.0 ±0.5	33.0 ±1.5	9,4
	KPL762533	3,7	600	7.6 ±0.2	25.0 ±0.5	33.0 ±1.5	10,6
**2535	KPL552535	3,7	430	5.5 ±0.2	25.0 ±0.5	35.0 ±1.5	8,5
**2540	KPL602540	3,7	580	6.0 ±0.2	25.0 ±0.5	40.0 ±1.5	11,0
**2550	KPL702550	3,7	800	7.0 ±0.2	25.0 ±0.5	50.0 ±1.5	12,8
	KPL802550	3,7	950	8.0 ±0.2	25.0 ±0.5	50.0 ±1.5	14,6
	KPL852550	3,7	1000	8.5 ±0.2	25.0 ±0.5	50.0 ±1.5	15,3
	KPL902550	3,7	1100	9.0 ±0.2	25.0 ±0.5	50.0 ±1.5	16,2
	KPL932550	3,7	1200	9.3 ±0.2	25.0 ±0.5	50.0 ±1.5	16,7

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
*2626	KPL452626	3,7	230	4.5 ±0.2	26.0 ±0.5	26.0 ±1.5	5,0
**2631	KPL302631	3,7	220	3.0 ±0.2	26.0 ±0.5	31.0 ±1.5	4,3
	KPL652631	3,7	460	6.5 ±0.2	26.0 ±0.5	31.0 ±1.5	9,0
**2634	KPL452634	3,7	380	4.5 ±0.2	26.0 ±0.5	34.0 ±1.5	7,2
**2652	KPL602652	3,7	800	6.0 ±0.2	26.0 ±0.5	52.0 ±1.5	15,8
**2663	KPL602663	3,7	1000	6.0 ±0.2	26.0 ±0.5	63.0 ±1.5	19,8
**2734	KPL852734	3,7	750	8.5 ±0.2	27.0 ±0.5	34.0 ±1.5	13,5
**2739	KPL402739	3,7	400	4.0 ±0.2	27.0 ±0.5	39.0 ±1.5	8,0
**2742	KPL502742	3,7	580	5.0 ±0.2	27.0 ±0.5	42.0 ±1.5	10,8
	KPL752742	3,7	800	7.5 ±0.2	27.0 ±0.5	42.0 ±1.5	15,7
**2745	KPL902745	3,7	1100	9.0 ±0.2	27.0 ±0.5	45.0 ±1.5	20,5
**2775	KPL372775	3,7	750	3.7 ±0.2	27.0 ±0.5	75.0 ±1.5	15,5
**2834	KPL682834	3,7	600	6.8 ±0.2	28.0 ±0.5	34.0 ±1.5	11,6
**2844	KPL802844	3,7	1000	8.0 ±0.2	28.0 ±0.5	44.0 ±1.5	18,6
**2880	KPL432880	3,7	1000	4.3 ±0.2	28.0 ±0.5	80.0 ±1.5	21,0
**2897	KPL602897	3,7	1800	6.0 ±0.2	28.0 ±0.5	97.0 ±1.5	34,7
**2927	KPL372927	3,7	320	3.7 ±0.2	29.0 ±0.5	27.0 ±1.5	4,8
**2934	KPL902934	3,7	850	9.0 ±0.2	29.0 ±0.5	34.0 ±1.5	15,6
**2944	KPL602944	3,7	800	6.0 ±0.2	29.0 ±0.5	44.0 ±1.5	14,6
**2950	KPL652950	3,7	900	6.5 ±0.2	29.0 ±0.5	50.0 ±1.5	18,6
**2952	KPL672952	3,7	1100	6.7 ±0.2	29.0 ±0.5	52.0 ±1.5	20,0
**2990	KPL702990	3,7	1900	7.0 ±0.2	29.0 ±0.5	90.0 ±1.5	39,0
**29127	KPL3829127	3,7	1650	3.8 ±0.2	29.0 ±0.5	127.0 ±1.5	31,5
	KPL6029127	3,7	2500	6.0 ±0.2	29.0 ±0.5	127.0 ±1.5	48,0
**3030	KPL353030	3,7	250	3.5 ±0.2	30.0 ±0.5	30.0 ±1.5	5,5
	KPL453030	3,7	360	4.5 ±0.2	30.0 ±0.5	30.0 ±1.5	7,1

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**3030	KPL503030	3,7	400	5.0 ±0.2	30.0 ±0.5	30.0 ±1.5	7,9
	KPL563030	3,7	480	5.6 ±0.2	30.0 ±0.5	30.0 ±1.5	8,8
	KPL603030	3,7	520	6.0 ±0.2	30.0 ±0.5	30.0 ±1.5	9,3
	KPL683030	3,7	590	6.8 ±0.2	30.0 ±0.5	30.0 ±1.5	10,6
**3035	KPL303035	3,7	280	3.0 ±0.2	30.0 ±0.5	35.0 ±1.5	5,9
	KPL403035	3,7	380	4.0 ±0.2	30.0 ±0.5	35.0 ±1.5	7,6
	KPL503035	3,7	500	5.0 ±0.2	30.0 ±0.5	35.0 ±1.5	9,8
	KPL603035	3,7	600	6.0 ±0.2	30.0 ±0.5	35.0 ±1.5	11,4
**3040	KPL203040	3,7	210	2.0 ±0.2	30.0 ±0.5	40.0 ±1.5	4,4
	KPL303040	3,7	330	3.0 ±0.2	30.0 ±0.5	40.0 ±1.5	7,0
	KPL353040	3,7	350	3.5 ±0.2	30.0 ±0.5	40.0 ±1.5	8,2
	KPL423040	3,7	450	4.2 ±0.2	30.0 ±0.5	40.0 ±1.5	9,7
	KPL503040	3,7	550	5.0 ±0.2	30.0 ±0.5	40.0 ±1.5	11,5
	KPL553040	3,7	630	5.5 ±0.2	30.0 ±0.5	40.0 ±1.5	12,5
	KPL603040	3,7	650	6.0 ±0.2	30.0 ±0.5	40.0 ±1.5	13,7
	KPL803040	3,7	950	8.0 ±0.2	30.0 ±0.5	40.0 ±1.5	17,9
	KPL903040	3,7	1000	9.0 ±0.2	30.0 ±0.5	40.0 ±1.5	19,9
**3045	KPL603045	3,7	850	6.0 ±0.2	30.0 ±0.5	45.0 ±1.5	15,6
	KPL743045	3,7	1020	7.4 ±0.2	30.0 ±0.5	45.0 ±1.5	19,2
	KPL763045	3,7	1080	7.6 ±0.2	30.0 ±0.5	45.0 ±1.5	19,5
**3048	KPL353048	3,7	500	3.5 ±0.2	30.0 ±0.5	48.0 ±1.5	10,3
	KPL403048	3,7	580	4.0 ±0.2	30.0 ±0.5	48.0 ±1.5	11,5
	KPL453048	3,7	650	4.5 ±0.2	30.0 ±0.5	48.0 ±1.5	12,8
	KPL503048	3,7	750	5.0 ±0.2	30.0 ±0.5	48.0 ±1.5	14,4
	KPL603048	3,7	850	6.0 ±0.2	30.0 ±0.5	48.0 ±1.5	16,9
	KPL653048	3,7	900	6.5 ±0.2	30.0 ±0.5	48.0 ±1.5	18,4

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**3048	KPL703048	3,7	1020	7.0 ±0.2	30.0 ±0.5	48.0 ±1.5	20,0
	KPL743048	3,7	1100	7.4 ±0.2	30.0 ±0.5	48.0 ±1.5	20,8
	KPL853048	3,7	1200	8.5 ±0.2	30.0 ±0.5	48.0 ±1.5	23,0
	KPL953048	3,7	1400	9.5 ±0.2	30.0 ±0.5	48.0 ±1.5	26,2
**3060	KPL503060	3,7	900	5.0 ±0.2	30.0 ±0.5	60.0 ±1.5	18,5
	KPL603060	3,7	1000	6.0 ±0.2	30.0 ±0.5	60.0 ±1.5	22,0
	KPL703060	3,7	1400	7.0 ±0.2	30.0 ±0.5	60.0 ±1.5	25,5
	KPL903060	3,7	1750	9.0 ±0.2	30.0 ±0.5	60.0 ±1.5	32,5
**3080	KPL703080	3,7	1800	7.0 ±0.2	30.0 ±0.5	80.0 ±1.5	36,0
**30158	KPL4030158	3,7	2100	4.0 ±0.2	30.0 ±0.5	158.0 ±1.5	41,7
**30160	KPL8030160	3,7	4100	8.0 ±0.2	30.0 ±0.5	160.0 ±1.5	85,0
**3157	KPL333157	3,7	520	3.3 ±0.2	31.0 ±0.5	57.0 ±1.5	12,0
**3233	KPL453233	3,7	500	4.5 ±0.2	32.0 ±0.5	33.0 ±1.5	8,6
	KPL103233	3,7	1020	10.0 ±0.2	32.0 ±0.5	33.0 ±1.5	18,5
**3247	KPL613247	3,7	1000	6.1 ±0.2	32.0 ±0.5	47.0 ±1.5	18,0
**3248	KPL453248	3,7	800	4.5 ±0.2	32.0 ±0.5	48.0 ±1.5	13,8
**3270	KPL803270	3,7	2000	8.0 ±0.2	32.0 ±0.5	70.0 ±1.5	37,2
**3285	KPL343285	3,7	950	3.4 ±0.2	32.0 ±0.5	85.0 ±1.5	19,6
**3337	KPL503337	3,7	750	5.0 ±0.2	33.0 ±0.5	37.0 ±1.5	11,5
**3342	KPL573342	3,7	820	5.7 ±0.2	33.0 ±0.5	42.0 ±1.5	15,1
**3434	KPL283434	3,7	260	2.8 ±0.2	34.0 ±0.5	34.0 ±1.5	5,9
**3436	KPL323436	3,7	320	3.2 ±0.2	34.0 ±0.5	36.0 ±1.5	7,4
**3442	KPL373442	3,7	480	3.7 ±0.2	34.0 ±0.5	42.0 ±1.5	10,2
	KPL403442	3,7	560	4.0 ±0.2	34.0 ±0.5	42.0 ±1.5	11,3
	KPL453442	3,7	650	4.5 ±0.2	34.0 ±0.5	42.0 ±1.5	12,5
	KPL503442	3,7	750	5.0 ±0.2	34.0 ±0.5	42.0 ±1.5	14,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**3442	KPL553442	3,7	800	5.5 ±0.2	34.0 ±0.5	42.0 ±1.5	15,2
	KPL653442	3,7	900	6.5 ±0.2	34.0 ±0.5	42.0 ±1.5	17,9
	KPL703442	3,7	1100	7.0 ±0.2	34.0 ±0.5	42.0 ±1.5	19,3
**3444	KPL603444	3,7	850	6.0 ±0.2	34.0 ±0.5	44.0 ±1.5	17,4
	KPL703444	3,7	1000	7.0 ±0.2	34.0 ±0.5	44.0 ±1.5	20,5
	KPL863444	3,7	1400	8.6 ±0.2	34.0 ±0.5	44.0 ±1.5	24,7
**3445	KPL353445	3,7	470	3.5 ±0.2	34.0 ±0.5	45.0 ±1.5	10,5
	KPL383445	3,7	550	3.8 ±0.2	34.0 ±0.5	45.0 ±1.5	11,5
	KPL563445	3,7	820	5.6 ±0.2	34.0 ±0.5	45.0 ±1.5	17,0
	KPL603445	3,7	1000	6.0 ±0.2	34.0 ±0.5	45.0 ±1.5	17,9
	KPL753445	3,7	1100	7.5 ±0.2	34.0 ±0.5	45.0 ±1.5	22,0
	KPL903445	3,7	1450	9.0 ±0.2	34.0 ±0.5	45.0 ±1.5	26,5
**3446	KPL803446	3,7	1350	8.0 ±0.2	34.0 ±0.5	46.0 ±1.5	24,4
**3448	KPL303448	3,7	500	3.0 ±0.2	34.0 ±0.5	48.0 ±1.5	9,5
	KPL523448	3,7	800	5.2 ±0.2	34.0 ±0.5	48.0 ±1.5	16,0
	KPL603448	3,7	1000	6.0 ±0.2	34.0 ±0.5	48.0 ±1.5	18,4
**3450	KPL303450	3,7	500	3.0 ±0.2	34.0 ±0.5	50.0 ±1.5	10,4
	KPL383450	3,7	650	3.8 ±0.2	34.0 ±0.5	50.0 ±1.5	13,0
	KPL403450	3,7	700	4.0 ±0.2	34.0 ±0.5	50.0 ±1.5	13,5
	KPL453450	3,7	820	4.5 ±0.2	34.0 ±0.5	50.0 ±1.5	15,4
	KPL503450	3,7	900	5.0 ±0.2	34.0 ±0.5	50.0 ±1.5	17,3
	KPL553450	3,7	1000	5.5 ±0.2	34.0 ±0.5	50.0 ±1.5	19,0
	KPL603450	3,7	1100	6.0 ±0.2	34.0 ±0.5	50.0 ±1.5	20,2
	KPL653450	3,7	1200	6.5 ±0.2	34.0 ±0.5	50.0 ±1.5	22,2
	KPL803450	3,7	1500	8.0 ±0.2	34.0 ±0.5	50.0 ±1.5	27,0
	KPL903450	3,7	1600	9.0 ±0.2	34.0 ±0.5	50.0 ±1.5	30,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**3450	KPL103450	3,7	1700	10.0 ±0.2	34.0 ±0.5	50.0 ±1.5	33,4
**3455	KPL383455	3,7	780	3.8 ±0.2	34.0 ±0.5	55.0 ±1.5	15,0
**3457	KPL823457	3,7	1650	8.2 ±0.2	34.0 ±0.5	57.0 ±1.5	32,0
**3465	KPL703465	3,7	1700	7.0 ±0.2	34.0 ±0.5	65.0 ±1.5	32,0
	KPL853465	3,7	1900	8.5 ±0.2	34.0 ±0.5	65.0 ±1.5	39,0
**3496	KPL643496	3,7	2200	6.4 ±0.2	34.0 ±0.5	96.0 ±1.5	45,0
**3535	KPL833535	3,7	950	8.3 ±0.2	35.0 ±0.5	35.0 ±1.5	18,5
	KPL103535	3,7	1100	10.0 ±0.2	35.0 ±0.5	35.0 ±1.5	22,0
**3562	KPL503562	3,7	1100	5.0 ±0.2	35.0 ±0.5	62.0 ±1.5	23,0
**3568	KPL543668	3,7	1450	5.4 ±0.2	35.0 ±0.5	68.0 ±1.5	27,0
**35126	KPL5835126	3,7	3200	5.8 ±0.2	35.0 ±0.5	126.0 ±1.5	57,0
**3657	KPL583657	3,7	1250	5.8 ±0.2	35.0 ±0.5	57.0 ±1.5	24,0
**3745	KPL623745	3,7	1200	6.2 ±0.2	35.0 ±0.5	45.0 ±1.5	20,5
**3756	KPL603756	3,7	1350	6.0 ±0.2	35.0 ±0.5	56.0 ±1.5	25,4
**3759	KPL303759	3,7	700	3.0 ±0.2	37.0 ±0.5	59.0 ±1.5	13,9
	KPL363759	3,7	830	3.6 ±0.2	37.0 ±0.5	59.0 ±1.5	16,5
	KPL503759	3,7	1200	5.0 ±0.2	37.0 ±0.5	59.0 ±1.5	23,0
	KPL533759	3,7	1250	5.3 ±0.2	37.0 ±0.5	59.0 ±1.5	27,0
	KPL583759	3,7	1400	5.8 ±0.2	37.0 ±0.5	59.0 ±1.5	25,6
	KPL603759	3,7	1500	6.0 ±0.2	37.0 ±0.5	59.0 ±1.5	27,0
	KPL783759	3,7	1800	7.8 ±0.2	37.0 ±0.5	59.0 ±1.5	34,7
	KPL903759	3,7	2200	9.0 ±0.2	37.0 ±0.5	59.0 ±1.5	40,0
**3762	KPL463762	3,7	1200	4.6 ±0.2	37.0 ±0.5	59.0 ±1.5	22,8
	KPL573762	3,7	1500	5.7 ±0.2	37.0 ±0.5	59.0 ±1.5	27,0
**37107	KPL4837107	3,7	2000	4.8 ±0.2	37.0 ±0.5	107.0 ±1.5	42,0
	KPL5537107	3,7	2200	5.5 ±0.2	37.0 ±0.5	107.0 ±1.5	49,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Midelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**37107	KPL6037107	3,7	2500	6.0 ±0.2	37.0 ±0.5	107.0 ±1.5	52,5
**37110	KPL5537110	3,7	2200	5.5 ±0.2	37.0 ±0.5	110.0 ±1.5	50,0
	KPL6037110	3,7	2500	6.0 ±0.2	37.0 ±0.5	110.0 ±1.5	54,0
**3843	KPL713848	3,7	1400	7.1 ±0.2	38.0 ±0.5	48.0 ±1.5	26,0
	KPL903848	3,7	1700	9.0 ±0.2	38.0 ±0.5	48.0 ±1.5	32,5
**3860	KPL723860	3,7	1800	7.2 ±0.2	38.0 ±0.5	60.0 ±1.5	34,0
	KPL803860	3,7	2000	8.0 ±0.2	38.0 ±0.5	60.0 ±1.5	37,7
**3943	KPL503943	3,7	800	5.0 ±0.2	39.0 ±0.5	43.0 ±1.5	16,5
**3944	KPL703944	3,7	1350	7.0 ±0.2	39.0 ±0.5	44.0 ±1.5	24,0
**3947	KPL533947	3,7	1050	5.3 ±0.2	39.0 ±0.5	47.0 ±1.5	19,0
**4041	KPL614041	3,7	1050	6.1 ±0.2	40.0 ±0.5	41.0 ±1.5	18,9
**4052	KPL384052	3,7	820	3.8 ±0.2	40.0 ±0.5	52.0 ±1.5	16,5
	KPL504052	3,7	1100	5.0 ±0.2	40.0 ±0.5	52.0 ±1.5	21,5
**4053	KPL604053	3,7	1400	6.0 ±0.2	40.0 ±0.5	53.0 ±1.5	26,0
	KPL854053	3,7	1600	8.5 ±0.2	40.0 ±0.5	53.0 ±1.5	36,5
**4057	KPL464057	3,7	1100	4.6 ±0.2	40.0 ±0.5	57.0 ±1.5	21,5
	KPL504057	3,7	1200	5.0 ±0.2	40.0 ±0.5	57.0 ±1.5	24,0
**4068	KPL504068	3,7	1450	5.0 ±0.2	40.0 ±0.5	68.0 ±1.5	29,5
**4069	KPL354069	3,7	900	3.5 ±0.2	40.0 ±0.5	69.0 ±1.5	21,0
	KPL384069	3,7	1150	3.8 ±0.2	40.0 ±0.5	69.0 ±1.5	22,0
	KPL404069	3,7	1200	4.0 ±0.2	40.0 ±0.5	69.0 ±1.5	23,5
**4078	KPL504078	3,7	1600	5.0 ±0.2	40.0 ±0.5	78.0 ±1.5	34,0
**4139	KPL764139	3,7	1200	7.6 ±0.2	41.0 ±0.5	39.0 ±1.5	23,0
**4155	KPL724155	3,7	1680	7.2 ±0.2	41.0 ±0.5	55.0 ±1.5	33,5
	KPL754155	3,7	1750	7.5 ±0.2	41.0 ±0.5	55.0 ±1.5	34,5
**4166	KPL654166	3,7	2000	6.5 ±0.2	41.0 ±0.5	66.0 ±1.5	37,5

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**4167	KPL304167	3,7	850	3.0 ±0.2	41.0 ±0.5	67.0 ±1.5	17,8
	KPL604167	3,7	1800	6.0 ±0.2	41.0 ±0.5	67.0 ±1.5	34,8
	KPL104167	3,7	3000	10.0 ±0.2	41.0 ±0.5	67.0 ±1.5	58,0
**4169	KPL454169	3,7	1300	4.5 ±0.2	41.0 ±0.5	69.0 ±1.5	27,0
	KPL504169	3,7	1450	5.0 ±0.2	41.0 ±0.5	69.0 ±1.5	30,8
	KPL654169	3,7	2000	6.5 ±0.2	41.0 ±0.5	69.0 ±1.5	39,5
**4250	KPL864250	3,7	1650	8.6 ±0.2	42.0 ±0.5	50.0 ±1.5	36,5
**4260	KPL704260	3,7	2200	7.0 ±0.2	42.0 ±0.5	60.0 ±1.5	37,5
**4265	KPL964265	3,7	3200	9.6 ±0.2	42.0 ±0.5	65.0 ±1.5	55,5
**4269	KPL964269	3,7	2950	9.6 ±0.2	42.0 ±0.5	69.0 ±1.5	52,8
**4275	KPL854275	3,7	3100	8.5 ±0.2	42.0 ±0.5	75.0 ±1.5	58,0
**4289	KPL384289	3,7	1450	3.8 ±0.2	42.0 ±0.5	89.0 ±1.5	32,0
	KPL504289	3,7	2100	5.0 ±0.2	42.0 ±0.5	89.0 ±1.5	42,0
**42113	KPL6842113	3,7	3600	4.5 ±0.2	42.0 ±0.5	113.0 ±1.5	73,0
**42140	KPL4542140	3,7	3500	4.5 ±0.2	42.0 ±0.5	140.0 ±1.5	60,5
**4359	KPL534359	3,7	1450	5.3 ±0.2	43.0 ±0.5	59.0 ±1.5	28,0
	KPL804359	3,7	2200	8.0 ±0.2	43.0 ±0.5	59.0 ±1.5	42,3
**4360	KPL304360	3,7	700	3.0 ±0.2	43.0 ±0.5	60.0 ±1.5	16,5
	KPL624360	3,7	1500	6.2 ±0.2	43.0 ±0.5	60.0 ±1.5	33,5
	KPL674360	3,7	1950	6.7 ±0.2	43.0 ±0.5	60.0 ±1.5	37,0
	KPL854360	3,7	2350	8.5 ±0.2	43.0 ±0.5	60.0 ±1.5	46,0
**4364	KPL284364	3,7	750	2.8 ±0.2	43.0 ±0.5	64.0 ±1.5	16,0
**4370	KPL824370	3,7	2600	8.2 ±0.2	43.0 ±0.5	70.0 ±1.5	53,0
	KPL884370	3,7	2800	8.8 ±0.2	43.0 ±0.5	70.0 ±1.5	56,0
**4380	KPL784380	3,7	2900	7.8 ±0.2	43.0 ±0.5	80.0 ±1.5	57,6
**4388	KPL804388	3,7	3480	8.0 ±0.2	43.0 ±0.5	88.0 ±1.5	66,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**4450	KPL854450	3,7	2000	8.5 ±0.2	44.0 ±0.5	50.0 ±1.5	38,0
	KPL904450	3,7	2200	9.0 ±0.2	44.0 ±0.5	50.0 ±1.5	40,0
	KPL954450	3,7	2300	9.5 ±0.2	44.0 ±0.5	50.0 ±1.5	42,0
**4455	KPL374455	3,7	1000	3.7 ±0.2	44.0 ±0.5	55.0 ±1.5	18,5
**4460	KPL504460	3,7	1450	5.0 ±0.2	44.0 ±0.5	60.0 ±1.5	28,0
**4472	KPL804472	3,7	2800	8.0 ±0.2	44.0 ±0.5	72.0 ±1.5	54,5
**4565	KPL524565	3,7	1600	5.2 ±0.2	45.0 ±0.5	65.0 ±1.5	31,0
**4654	KPL804654	3,7	2200	8.0 ±0.2	46.0 ±0.5	54.0 ±1.5	41,0
**4671	KPL534671	3,7	2000	5.3 ±0.2	46.0 ±0.5	71.0 ±1.5	37,0
**4677	KPL444677	3,7	2000	4.4 ±0.2	46.0 ±0.5	77.0 ±1.5	34,5
**4699	KPL604699	3,7	2850	6.0 ±0.2	46.0 ±0.5	99.0 ±1.5	61,0
**46102	KPL4546102	3,7	2500	4.5 ±0.2	46.0 ±0.5	102.0 ±1.5	47,5
**46146	KPL4546146	3,7	3400	4.5 ±0.2	46.0 ±0.5	146.0 ±1.5	70,0
**4759	KPL854759	3,7	2500	8.5 ±0.2	47.0 ±0.5	59.0 ±1.5	50,0
**4761	KPL604761	3,7	1900	6.0 ±0.2	47.0 ±0.5	61.0 ±1.5	36,5
**4763	KPL704763	3,7	2250	7.0 ±0.2	47.0 ±0.5	63.0 ±1.5	44,0
**4771	KPL474771	3,7	1700	4.7 ±0.2	47.0 ±0.5	71.0 ±1.5	33,5
	KPL964771	3,7	3800	9.6 ±0.2	47.0 ±0.5	71.0 ±1.5	69,0
**4783	KPL504783	3,7	2100	5.0 ±0.2	47.0 ±0.5	83.0 ±1.5	43,5
**47109	KPL8047109	3,7	5000	8.0 ±0.2	47.0 ±0.5	109.0 ±1.5	92,5
**4854	KPL454854	3,7	1550	4.5 ±0.2	48.0 ±0.5	54.0 ±1.5	24,3
	KPL464854	3,7	1700	4.6 ±0.2	48.0 ±0.5	54.0 ±1.5	25,0
**4856	KPKL784856	3,7	2200	7.8 ±0.2	48.0 ±0.5	56.0 ±1.5	43,5
**4860	KPL654860	3,7	2000	6.5 ±0.2	48.0 ±0.5	60.0 ±1.5	40,0
	KPL784860	3,7	2400	7.8 ±0.2	48.0 ±0.5	60.0 ±1.5	47,0
	KPL824860	3,7	2800	8.2 ±0.2	48.0 ±0.5	60.0 ±1.5	50,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**4860	KPL904860	3,7	3000	9.0 ±0.2	48.0 ±0.5	60.0 ±1.5	54,5
**4872	KPL364872	3,7	1350	3.6 ±0.2	48.0 ±0.5	72.0 ±1.5	27,0
	KPL464872	3,7	1800	4.6 ±0.2	48.0 ±0.5	72.0 ±1.5	34,0
**4942	KPL364942	3,7	800	3.6 ±0.2	49.0 ±0.5	42.0 ±1.5	14,5
**5048	KPL605048	3,7	1600	6.0 ±0.2	50.0 ±0.5	48.0 ±1.5	29,5
**5056	KPL685056	3,7	2100	6.8 ±0.2	50.0 ±0.5	56.0 ±1.5	40,0
	KPL955056	3,7	2750	9.5 ±0.2	50.0 ±0.5	56.0 ±1.5	55,0
**5060	KPL655060	3,7	2000	6.5 ±0.2	50.0 ±0.5	60.0 ±1.5	41,5
**5065	KPL505065	3,7	1800	5.0 ±0.2	50.0 ±0.5	65.0 ±1.5	35,0
**5067	KPL625067	3,7	2550	6.2 ±0.2	50.0 ±0.5	67.0 ±1.5	45,0
**5068	KPL425068	3,7	1600	4.2 ±0.2	50.0 ±0.5	68.0 ±1.5	31,0
	KPL485068	3,7	1800	4.8 ±0.2	50.0 ±0.5	68.0 ±1.5	35,0
	KPL495068	3,7	1900	4.9 ±0.2	50.0 ±0.5	68.0 ±1.5	36,5
	KPL555068	3,7	2000	5.5 ±0.2	50.0 ±0.5	68.0 ±1.5	41,0
	KPL805068	3,7	3000	8.0 ±0.2	50.0 ±0.5	68.0 ±1.5	58,5
**5080	KPL935080	3,7	4600	9.3 ±0.2	50.0 ±0.5	80.0 ±1.5	70,0
**5082	KPL395082	3,7	1800	3.9 ±0.2	50.0 ±0.5	82.0 ±1.5	35,5
**5085	KPL435085	3,7	2000	4.3 ±0.2	50.0 ±0.5	85.0 ±1.5	40,0
	KPL455085	3,7	2100	4.5 ±0.2	50.0 ±0.5	85.0 ±1.5	42,5
	KPL465085	3,7	2500	4.6 ±0.2	50.0 ±0.5	85.0 ±1.5	44,0
	KPL525085	3,7	2600	5.2 ±0.2	50.0 ±0.5	85.0 ±1.5	49,5
	KPL545085	3,7	2700	5.4 ±0.2	50.0 ±0.5	85.0 ±1.5	51,0
	KPL605085	3,7	3000	6.0 ±0.2	50.0 ±0.5	85.0 ±1.5	56,0
	KPL705085	3,7	3400	7.0 ±0.2	50.0 ±0.5	85.0 ±1.5	67,0
	KPL805085	3,7	3800	8.0 ±0.2	50.0 ±0.5	85.0 ±1.5	75,0
	KPL855085	3,7	4100	8.5 ±0.2	50.0 ±0.5	85.0 ±1.5	80,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

GPBM Industry
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**5085	KPL885085	3,7	4200	8.8 ±0.2	50.0 ±0.5	85.0 ±1.5	83,0
	KPL955085	3,7	4800	9.5 ±0.2	50.0 ±0.5	85.0 ±1.5	88,5
	KPL105085	3,7	5000	10.0 ±0.2	50.0 ±0.5	85.0 ±1.5	94,0
**50100	KPL3650100	3,7	2000	3.6 ±0.2	50.0 ±0.5	100.0 ±1.5	40,7
**50112	KPL5350112	3,7	3350	5.3 ±0.2	50.0 ±0.5	112.0 ±1.5	68,0
**5150	KPL345150	3,7	2300	3.4 ±0.2	51.0 ±0.5	50.0 ±1.5	17,5
**5158	KPL585158	3,7	1950	5.8 ±0.2	51.0 ±0.5	58.0 ±1.5	37,0
**5165	KPL555165	3,7	2100	5.5 ±0.2	51.0 ±0.5	65.0 ±1.5	39,0
**5166	KPL405166	3,7	1800	4.0 ±0.2	51.0 ±0.5	66.0 ±1.5	28,5
**5181	KPL865181	3,7	4100	8.6 ±0.2	51.0 ±0.5	81.0 ±1.5	78,0
**5255	KPL805255	3,7	2750	8.0 ±0.2	52.0 ±0.5	55.0 ±1.5	47,7
**5257	KPL445257	3,7	1700	4.4 ±0.2	52.0 ±0.5	57.0 ±1.5	27,0
**5262	KPL555262	3,7	1850	5.5 ±0.2	52.0 ±0.5	62.0 ±1.5	38,0
	KPL755262	3,7	2500	7.5 ±0.2	52.0 ±0.5	62.0 ±1.5	51,0
**5278	KPL405278	3,7	1900	4.0 ±0.2	52.0 ±0.5	78.0 ±1.5	35,0
**52101	KPL3552101	3,7	2000	3.5 ±0.2	52.0 ±0.5	101.0 ±1.5	42,0
	KPL5852101	3,7	3200	5.8 ±0.2	52.0 ±0.5	101.0 ±1.5	67,5
**5353	KPL445353	3,7	1650	4.4 ±0.2	53.0 ±0.5	53.0 ±1.5	26,0
**5363	KPL755363	3,7	3000	7.5 ±0.2	53.0 ±0.5	63.0 ±1.5	43,5
**5365	KPL675365	3,7	3000	6.7 ±0.2	53.0 ±0.5	65.0 ±1.5	50,0
**5373	KPL705373	3,7	3300	7.0 ±0.2	53.0 ±0.5	73.0 ±1.5	60,0
**5386	KPL105386	3,7	6000	10.0 ±0.2	53.0 ±0.5	86.0 ±1.5	101,0
**53155	KPL3053155	3,7	3000	3.0 ±0.2	53.0 ±0.5	155.0 ±1.5	57,7
**5462	KPL555462	3,7	200	5.5 ±0.2	54.0 ±0.5	62.0 ±1.5	39,0
	KPL705462	3,7	2580	7.0 ±0.2	54.0 ±0.5	62.0 ±1.5	50,0
	KPL805462	3,7	3000	8.0 ±0.2	54.0 ±0.5	62.0 ±1.5	57,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argogatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Midelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**5486	KPL905486	3,7	4100	9.0 ±0.2	54.0 ±0.5	86.0 ±1.5	92,5
**54102	KPL3654102	3,7	2500	3.6 ±0.2	54.0 ±0.5	102.0 ±1.5	45,0
**5545	KPL455545	3,7	1200	4.5 ±0.2	55.0 ±0.5	45.0 ±1.5	22,5
**5558	KPL325558	3,7	1150	3.2 ±0.2	55.0 ±0.5	58.0 ±1.5	21,0
**5566	KPL445566	3,7	2000	4.4 ±0.2	55.0 ±0.5	66.0 ±1.5	34,0
**5570	KPL885570	3,7	3900	8.8 ±0.2	55.0 ±0.5	70.0 ±1.5	73,0
	KPL905570	3,7	4000	9.0 ±0.2	55.0 ±0.5	70.0 ±1.5	75,0
**5575	KPL305575	3,7	1500	3.0 ±0.2	55.0 ±0.5	75.0 ±1.5	27,4
**5597	KPL485597	3,7	3000	4.8 ±0.2	55.0 ±0.5	97.0 ±1.5	57,8
**5670	KPL345670	3,7	1750	3.4 ±0.2	56.0 ±0.5	70.0 ±1.5	28,5
**5679	KPL805679	3,7	4500	8.0 ±0.2	56.0 ±0.5	79.0 ±1.5	78,0
**56156	KPL3256156	3,7	3100	3.2 ±0.2	56.0 ±0.5	156.0 ±1.5	64,0
**5770	KPL355770	3,7	1600	5.7 ±0.2	57.0 ±0.5	70.0 ±1.5	29,5
**5778	KPL455778	3,7	2600	4.5 ±0.2	52.0 ±0.5	62.0 ±1.5	44,0
**5784	KPL555784	3,7	2950	5.5 ±0.2	57.0 ±0.5	84.0 ±1.5	58,0
*57123	KPL3057123	3,7	2300	3.0 ±0.2	57.0 ±0.5	123.0 ±1.5	48,5
**5879	KPL485879	3,7	3000	4.8 ±0.2	58.0 ±0.5	79.0 ±1.5	48,7
**58110	KPL6558110	3,7	4200	6.5 ±0.2	58.0 ±0.5	110.0 ±1.5	95,0
	KPL7258110	3,7	5200	7.2 ±0.2	58.0 ±0.5	110.0 ±1.5	105,0
**58120	KPL4158120	3,7	3500	4.1 ±0.2	58.0 ±0.5	120.0 ±1.5	67,0
**58123	KPL2858123	3,7	2500	2.8 ±0.2	58.0 ±0.5	123.0 ±1.5	44,7
**5973	KPL385973	3,7	2300	3.8 ±0.2	59.0 ±0.5	73.0 ±1.5	36,0
**59111	KPL4259111	3,7	3300	4.2 ±0.2	59.0 ±0.5	111.0 ±1.5	63,0
**6066	KPL656066	3,7	3100	6.5 ±0.2	60.0 ±0.5	66.0 ±1.5	56,0
**6071	KPL366071	3,7	2100	3.6 ±0.2	60.0 ±0.5	71.0 ±1.5	33,7
**6080	KPL376080	3,7	2300	3.7 ±0.2	60.0 ±0.5	80.0 ±1.5	39,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**6090	KPL606090	3,7	3700	6.0 ±0.2	60.0 ±0.5	90.0 ±1.5	72,5
	KPL806090	3,7	5000	8.0 ±0.2	60.0 ±0.5	90.0 ±1.5	97,0
**6091	KPL776091	3,7	5000	7.7 ±0.2	60.0 ±0.5	91.0 ±1.5	98,5
**60100	KPL4060100	3,7	3000	4.0 ±0.2	60.0 ±0.5	100.0 ±1.5	54,0
**6275	KPL326275	3,7	1400	3.2 ±0.2	62.0 ±0.5	75.0 ±1.5	33,0
**62107	KPL4562107	3,7	3000	6.2 ±0.2	62.0 ±0.5	107.0 ±1.5	68,0
**6381	KPL386381	3,7	2500	3.8 ±0.2	63.0 ±0.5	81.0 ±1.5	44,0
	KPL426381	3,7	2800	4.2 ±0.2	63.0 ±0.5	81.0 ±1.5	47,8
**6386	KPL406386	3,7	2500	4.0 ±0.2	63.0 ±0.5	86.0 ±1.5	47,6
**6387	KPL456387	3,7	3000	4.5 ±0.2	63.0 ±0.5	87.0 ±1.5	88,0
**63133	KPL3763133	3,7	3400	3.7 ±0.2	63.0 ±0.5	133.0 ±1.5	70,5
**6478	KPL486478	3,7	2500	4.8 ±0.2	64.0 ±0.5	78.0 ±1.5	53,0
	KPL566478	3,7	3000	5.6 ±0.2	64.0 ±0.5	78.0 ±1.5	62,0
**64130	KPL3564130	3,7	3500	6.4 ±0.2	64.0 ±0.5	130.0 ±1.5	65,0
**6570	KPL966570	3,7	5000	9.6 ±0.2	65.0 ±0.5	70.0 ±1.5	95,0
**6573	KPL366573	3,7	1800	3.6 ±0.2	65.0 ±0.5	73.0 ±1.5	37,9
**6576	KPL906576	3,7	4700	9.0 ±0.2	65.0 ±0.5	76.0 ±1.5	98,0
**6666	KPL416666	3,7	2300	4.1 ±0.2	66.0 ±0.5	66.0 ±1.5	39,0
**6770	KPL706770	3,7	3700	7.0 ±0.2	67.0 ±0.5	70.0 ±1.5	71,5
**67112	KPL3567112	3,7	3100	3.5 ±0.2	67.0 ±0.5	112.0 ±1.5	61,5
	KPL3867112	3,7	3400	3.8 ±0.2	67.0 ±0.5	112.0 ±1.5	66,0
**68140	KPL3568140	3,7	4000	3.5 ±0.2	68.0 ±0.5	140.0 ±1.5	77,0
**6987	KPL406987	3,7	2900	4.0 ±0.2	69.0 ±0.5	87.0 ±1.5	53,0
**69100	KPL3969100	3,7	3200	3.9 ±0.2	69.0 ±0.5	100.0 ±1.5	62,0
	KPL4069100	3,7	3350	4.0 ±0.2	69.0 ±0.5	100.0 ±1.5	63,0
**69110	KPL3669110	3,7	3000	3.6 ±0.2	69.0 ±0.5	110.0 ±1.5	63,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argogatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middeelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no

SPECIFICATIONS

Type	Model No.	Nominal Voltage (V)	Nominal Capacity (mAh)	Dimensions (mm) (Thickness / Width / Length)			Weight (g)
**7093	KPL447093	3,7	3100	4.4 ±0.2	70.0 ±0.5	93.0 ±1.5	64,0
**7097	KPL357097	3,7	3000	3.5 ±0.2	70.0 ±0.5	97.0 ±1.5	53,0
**7280	KPL367280	3,7	2500	3.6 ±0.2	72.0 ±0.5	80.0 ±1.5	46,6
**7290	KPL317290	3,7	2400	3.1 ±0.2	72.0 ±0.5	90.0 ±1.5	44,5
**7390	KPL487390	3,7	3650	4.8 ±0.2	73.0 ±0.5	90.0 ±1.5	71,5
**7580	KPL767580	3,7	5500	7.6 ±0.2	75.0 ±0.5	80.0 ±1.5	101,0
**7590	KPL407590	3,7	3000	4.0 ±0.2	75.0 ±0.5	90.0 ±1.5	60,0
**7591	KPL437591	3,7	3600	4.3 ±0.2	75.0 ±0.5	91.0 ±1.5	66,0
**7595	KPL307595	3,7	2400	3.0 ±0.2	75.0 ±0.5	95.0 ±1.5	49,0
	KPL407595	3,7	2850	4.0 ±0.2	75.0 ±0.5	95.0 ±1.5	64,0
**7688	KPL387688	3,7	3100	3.8 ±0.2	76.0 ±0.5	88.0 ±1.5	58,0
**7696	KPL407696	3,7	3300	4.0 ±0.2	76.0 ±0.5	96.0 ±1.5	65,0
**76111	KPL3276111	3,7	3000	3.2 ±0.2	76.0 ±0.5	111.0 ±1.5	60,0
**7886	KPL367886	3,7	3000	3.6 ±0.2	78.0 ±0.5	86.0 ±1.5	55,0
**8290	KPL398290	3,7	3200	3.9 ±0.2	82.0 ±0.5	90.0 ±1.5	67,0
**8999	KPL388999	3,7	4000	3.8 ±0.2	89.0 ±0.5	99.0 ±1.5	76,0
**90120	KPL3790120	3,7	4500	3.7 ±0.2	90.0 ±0.5	120.0 ±1.5	93,0
**90125	KPL3390125	3,7	4300	3.3 ±0.2	90.0 ±0.5	125.0 ±1.5	87,0
**9493	KPL489493	3,7	4700	4.8 ±0.2	94.0 ±0.5	93.0 ±1.5	96,0
**98140	KPL3598140	3,7	6000	3.5 ±0.2	98.0 ±0.5	140.0 ±1.5	115,0
**100104	KPL32100104	3,7	3900	3.2 ±0.2	100.0 ±0.5	104.0 ±1.5	77,5
**103120	KPL37103120	3,7	4000	3.7 ±0.2	103.0 ±0.5	120.0 ±1.5	78,0
**105103	KPL38105103	3,7	5200	3.8 ±0.2	105.0 ±0.5	103.0 ±1.5	95,0

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

 **GPBM Industry**
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no