

GP NiMH Standard Series

GP rechargeable NiMH Standard Series batteries. Suitable for a wide range of applications such as smart home cameras and portable devices.



The standard series is a general helper, as they can be used in a wide range of applications. It delivers balanced performance between charge retention, power discharge and cycle life. It's optimized formulation is capable to deliver one of the highest energy capacity among all of the competition.

FEATURES

- Low self discharge
- Excellent charge retention
- Produced in a fully automated production line for exceptional cell consistency
- Safe chemistry
- Not restricted in air transport
- Recyclable

APPLICATIONS

- Cordless phones
- Portable devices
- Flashlights
- Baby monitors
- Photographic devices
- Remote controls
- Transceivers
- Personal care devices
- Video/audio devices

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

Cell Size		Model	Diameter	Height	Nominal Voltage (V)	Rated Capacity (mAh)	Typical Capacity (mAh)	Approx. Weight (g)	LSD Type
AAAA	5/4AAAA	GP50AAALH	8.6	52.6	1.2	500	520	9.5	L80-1
AAA	1/3AAA	GP17AAAH	10.4	14.1	1.2	170	180	4.2	L80-1
	2/3AAA	GP30AAAM	10.4	29.3	1.2	300	300	7.5	L80-1
	2/3AAA	GP40AAAM	10.4	29.3	1.2	400	420	8.0	L80-1
	AAA	GP50AAAH	10.5	43.7	1.2	500	520	10.5	L80-1
	AAA	GP50AAAHC	10.5	44.5	1.2	500	520	12.0	L80-1
	AAA	GP55AAAH	10.5	43.7	1.2	550	580	13.0	L80-1
	AAA	GP60AAAH	10.5	43.7	1.2	600	630	13.0	L80-1
	AAA	GP65AAAH	10.5	43.7	1.2	650	680	13.0	L80-1
	AAA	GP70AAAH	10.5	43.7	1.2	700	730	13.0	L80-1
	AAA	GP75AAAH	10.5	43.7	1.2	750	780	13.0	L80-1
	AAA	GP80AAAH	10.5	43.7	1.2	800	830	13.0	L80-1
	AAA	GP95AAAH	10.5	43.7	1.2	900	930	15.2	L80-1
	AAA	GP91AAALH	10.5	50.0	1.2	910	930	15.1	L80-1
AA	2/3AA	GP60AAH	14.5	28.7	1.2	600	620	14.0	L80-1
	2/3AA	GP75AAH	14.5	28.7	1.2	750	770	15.0	L80-1
	AA	GP60AAM	14.4	48.2	1.2	600	820	15.5	L80-1
	AA	GP70AAMD	14.4	48.2	1.2	700	730	17.0	L80-1
	AA	GP90AAMD	14.4	48.2	1.2	900	930	20.0	L80-1
	AA	GP130AAM	14.4	48.2	1.2	1300	1350	25.0	L80-1
	AA	GP150AAM	14.4	48.2	1.2	1500	1550	26.0	L80-1
	AA	GP160AAH	14.4	48.2	1.2	1600	1650	26.0	L80-1
	AA	GP180AAH	14.5	49.2	1.2	1800	1850	28.0	L80-1
	AA	GP200AAH	14.5	49.2	1.2	2000	2050	29.5	L80-1
	AA	GP220AAH	14.5	49.2	1.2	220	2250	29.5	L80-1
AF	4/5AF	GP211AFH	17	43.0	1.2	2100	2160	33.0	L50-1
	AF	GP270AFH	17	50.0	1.2	2600	2700	39.5	L50-1
	7/5AF	GP380AFH	17	67.0	1.2	3800	3820	53.5	L50-1
LA	18670	GP380LAHV	18.3	67.0	1.2	3800	3990	60.0	L50-1
	18670	GP450LAH	18.3	67.0	1.2	4300	4500	63.0	L50-1
9V	9V	GP17R8H	15.7(T) X 26.5(W) X 48.5(H)		8.4	170	175	32.0	L80-1
	9V	GP17R9H	15.7(T) X 26.5(W) X 48.5(H)		9.6	170	175	36.0	L80-1

This is a non-contractual document. The information contained in this document is for descriptive purpose and should not be used as a basis for product guarantee or warranty.

GPBM Industry
Independent Energy Solutions

Sweden
GPBM Nordic AB
Argongatan 2B
431 53 Mölndal
Tel: +46 31-799 16 00
industry@gpbmnordic.se

Denmark
GPBM Nordic ApS
Middelfartvej 11 E
DK-5000 Odense C
Tel: +45 70 26 11 04
industry@gpbmnordic.dk

Finland
GPBM Nordic OY
Teknobulevardi 3-5
FI-01530 Vantaa
Tel: +358 2 478 10 00
industry@gpbmnordic.fi

France
GPBM France
64 ZAE du Trou Grillon, BP 49
91280 St. Pierre du Perray
Tél. : +33 1 69 89 62 00
info@gpbmfrance.fr

Italy
GPBM Italy S.R.L.
Via Alessandro Volta 3
20090 Assago Milano
Tel: +39 02 488 25 12
industry@gpbmitaly.it

Norway
GPBM Nordic AS
Prof. Birkelandsvei 26B
1001 Oslo,
Tel: +47 22 88 30 40
industry@gpbmnordic.no